

Industry and commercial storage

product model	picture	technical parameter	
50KW/100K Wh (without MPPT)		nominal voltage (V)	358.4
		charging voltage (V)	408.8
		Discharge protection voltage (V)	313.6
		Standard capacity 0.5C (Ah)	280
		energy (KWh)	100.352
		Rated output power [KW]	50
		Maximum continuous discharge current (A)	72
		working temperature (°C)	-20 to 55 degrees
		cooling method	forced air cooling
		product size (mm)	700mm×2250mm×1150mm(W*H*D)
		Packing dimensions (mm)	
		weight (Kg)	1500
product model	picture	technical parameter	
50KW/100K Wh (with MPPT)		nominal voltage (V)	358.4
		charging voltage (V)	408.8
		Discharge protection voltage (V)	313.6
		Standard capacity 0.5C (Ah)	280
		energy (KWh)	100.352
		Rated output power [KW]	50
		Maximum continuous discharge current (A)	72
		working temperature (°C)	-20 to 55 degrees
		cooling method	forced air cooling
		MPPT Operating voltage range [V]	150-850
		MPPT quantity	4
		Maximum input current [A]	4*40
		product size (mm)	700mm×2250mm×1150mm(W*H*D)
		Packing dimensions (mm)	
		weight (Kg)	1500